

Product Code

UTC-0750	Concrete Mixer Pan Type, 100 L, 220-240 V 50-60 Hz
UTC-0750/110	Concrete Mixer Pan Type, 100 L, 110 V 60 Hz
UTC-0752	Concrete Mixer Pan Type, Double-Acting Mix Equipped, 100 L. 380 V 50 Hz (If 220 V is required please mention at time of order)

Standards

EN 1766

The efficient mixing of concrete is essential if quality specimens are to be manufactured. The Pan Type Concrete Mixers are designed to give efficient mixing of both dry and wet materials.

The difference of UTC-0752 from conventional mixers (UTC-0750) is its ability of preparing more homogenous mixture in a short time through the second engine which rotates the stirring beater in the opposite direction of the mixing drum's rotation direction.

The mixing pan is removable and tilts for easy access to the pan and emptying on completion of the mixing operation. The total volume of the pan is 108 liters but the effective capacity of the mixer is 56 liters.

The mixer head lifts clear to provide maximum access to the pan and holds the mixing blades at a constant depth during the mixing operation. The blades can be adjusted to suit the different types and volume of materials to be mixed. The pan type mixer is also equipped with rubber wheels which provide high portability.

All parts of the IP55 protected mixer are noncorrosive painted and galvanized.

	UTC-0750	UTC-0752
Dimensions	950x1050x1250 mm	950x1050x1270 mm
Weight (approx.)	255 kg	285 kg
Power	1500 W	3300 W

